


MBT4060S Solid Door MBT4060G Glass Door

- Advanced Environmental Friendly Thermoelectric Cooling Technology
- Quite operation. No Fan and No vibration
- Two removable, adjustable metal shelves expand the storage space and make the fridge easy to clean
- Thermal insulation manufactured with Superior Cyclopentane
- Insulation free of CFC/HCFC
- Stocking capacity of up to 36 facings
- Fully Automatic Defrost Function
- Lower Energy Consumption than Absorption Systems
- Strong reversible door hinges, convertible to either left or right side
- Foaming Solid Door with two adjustable transparent racks
- Door is made with magnetic seals to keep it perfectly closed
- Easily Adjustable Electronic Thermostat for Ideal Temperature Control
- Soft LED Interior Light for more visibility
- Integrated Door Handles
- Free Standing or can be inserted into existing furniture
- Outer Body Black Color I Inner Body White Color





#### **Electrical information**

Input Voltage	220 – 240 V
Power	65 W
Input Frequency	50 – 60 Hz
Plugs	EU & BS

# **Product Performance**

Technology Environmental Friendly Thermoelectric Cooling Technology Cooling  $5 \,^{\circ}\text{C} \sim 8 \,^{\circ}\text{C}$  at 25  $^{\circ}$  room temperature (Solid)  $10 \,^{\circ}\text{C} \sim 15 \,^{\circ}\text{C}$  at 25  $^{\circ}\text{C}$  room temperature (Glass)

Refrigerant Amount 98 g

# **Additional Information**

Color Outer: Black I Inner: White
Finishes Solid Door / Glass Door
Certificates (EB RoHS Compliant Intertek CS)

# **Shipping Details**

 Carton (W x D x H)
 560 x 552 x 622 mm


 Gross Weight
 22.4 kg / 49.38 lb

 Net Weight
 20.2 kg / 44.53 lb

 Packaging
 01 pieces

 HS Code
 84182900

# **Drawing**



Box contents: MINIBAR, INSTALLATION GUIDE





